EZ LOCK Model TL-20





Model TL-20 fits all Hammerblow Bulldog style 1 $\frac{7}{8}$ inch, 2 inch and 2 $\frac{5}{16}$ inch trailer couplers and similar styles. Place slanted side toward front of coupler (marked front on lock). Insert pin. Attach your padlock. *Padlock not included*.

The TL-20 is simple to use, but built for rugged use.


EZ LOCK Model TL-33

Patent No. D4360645

Now one lock fits more than 30 couplers.

The EZ Lock Model TL-33 Universal Coupler Lock is precision made of heavy grade aircraft aluminum and will not rust. It features a 3/4" steel locking pin, for use with large heavy duty padlock Model TL-45 (not included).

It's as easy as 1-2-3... Use the guide below to determine which pin position to use for your particular trailer. Simply position the pin at the number indicated on the lock to fit your coupler.



Position #1
Fits all trigger style: Fulton, Shelby,
Dutton-Lainson, Atwood and similar.



2,000 lb Trigger Style



Shelby 5,000 lb 2"



Fulton 5,000 lb 2"



Shelby Heavy Duty A-Frame 10,000 lb 2 5/16"



Atwood Latch Style 8,500 lb 2 5/16" (latch must be raised)



Fulton Handwheel U-Haul



Position #2
Fits latch style: Atwood, Fulton cast couplers and similar.



Atwood 5,000 lb Latch Style



Position #3
Fits large 8,000 and 10,000 lb. Atwood couplers used on many cargo style trailers.



Atwood 8,000 lb 2" No. 88555



Atwood 10,000 lb 2 5/16" No. 88007