

CARGO PROTECTORS, INC.

633 3RD Street NE, St. Cloud, MN 56304 www.cargoprotectors.com

Toll-Free: (800) 728-3038 Phone: (320) 202-6567 Fax: (320) 202-7792 sales@cargoprotectors.com

SL100 / SLX100 / S103 Door Hasp


High Security Hasp for Padlocks
Provides High Security for Doors

- Made from high carbon heat treated steel
- Heavy duty galvanized finish for weather resistance
- Small, medium, and large footprint assures the proper fit
- Mounting hardware included

SL100 Door Hasp



SLX100 Door Hasp



S103 Door Hasp



INSTALLATION INSTRUCTIONS

- 1. Make sure you have all required hardware: Hasp (both sides), Lock, Six 3/8" Carriage Bolts (SLX100) or Four 5/16" Carriage Bolts (SL100), Nuts, and Fender Washers.
 - a. Suggested item: Small vise grip pliers
- 2. Put hasp together as it will be installed on the doors making sure bottom is level.
- 3. Place a fender washer between the eyes of the hasp halves to maintain proper clearance and clamp together with the small vise grip pliers.
- 4. Using the clamped assembly as a template, mark the holes and drill 7/16" holes at the marked locations.
- 5. Remove vise grip pliers.
- 6. Install carriage bolts (length is determined by thickness of mounting surface), with washers and nuts.